



# Rapid Low Temperature Circulating Bath

LRTB-A60

## Rapid Low Temperature Circulating Bath LRTB-A60

Rapid Low Temperature Circulating Bath LRTB-A60 is a microcomputer controlled 10 L bath with refrigeration system and a temperature range of -40 °C to 200 °C. Equipped with dual red and green LED windows with upper window measuring red value and lower measuring green value. Features internal and external cycles with external cycles discharging thermostatic liquid outside the bath raising the temperature of the external vessel.

---

### Features

- ▶ Volume - 10 L
  - ▶ Low temperature cooling pump
  - ▶ Microcomputer controlled temperature
  - ▶ Temperature and time LCD display
  - ▶ Built-in liquid level monitor
  - ▶ Refrigeration unit with relay, protector and capacitor
  - ▶ Anti-corrosive circulatory system
- 

### Specifications

| Model No                        | LRTB-A60         |
|---------------------------------|------------------|
| Volume                          | 10 L             |
| Temperature range               | -40 °C to 200 °C |
| Refrigerating capacity          | 3610 W           |
| Pump flow                       | 20 L / min       |
| Temperature stability           | ±0.1 °C          |
| Head of delivery                | 10 m             |
| Temperature control tier number | 32               |
| Heating power                   | 2500 W           |